
Press bed

One of the accessories for all FlexiPress H-model and C-model is our press bed produced in high quality machined steel, the press bed/press plate is machined on all sides and equipped with T-slots in an X (see picture).



Press bed for FP og EP										
	2	25/40T	60/100T	150/200T						
Depth	А	300	400	500						
Width	В	500	600	700						
T-slot	C	14	14	18						

Tool Program



Clamping tool for fixing wire ends

Tool is made at Stenhøj. It consists of a tool rig + 3 different dies available for wire diameters Ø6, Ø8 & Ø10mm. Observe max pressing force: 40t.




With 8 different sizes of arbors Ø12, 14, 16, 18, 20, 22, 25 & 30mm. and adaptor for mounting the arbors to the cylinder head, plus a bracket (holder) to hang the arbors on the press frame side. Observe that there are 4 different adaptors.





Broaching fixture

It is the console only to hold the ring and make it easier for the process to get access to the needle. The customer provides the matrix and ring, which are individual for the various parts to make.



Used for pipe/tube bending with 6 different sizes matrixes – 3/8", 1/2", 3/4", 1", 5/4", $1^1/2$ " and 2 support blocks





With kidney-shaped hole. This is mostly used with ClassicPress & BenchPress for pressing out bearings (auto repair shops).



Guided Press brake attachment for bending of sheet metal

Suitable for FP40t up to 200t. working width of 835mm. the lower of this tool has got 4 different tracks 16, 25, 45 & 65mm, wedge angel of 90°, for sheet metal from 0,5 to 6mm.

