

Rechargeable battery clinch and pierce unit ULBG 601

BTM

[Europe]
Blechverbindungstechnik
GmbH



**Exchangeable
tool holder!**



Battery &
main operation



Single-hand
control

Features:

- **Capable to clinch** total thickness of 6 mm steel or aluminium
- **Use for clinching** or piercing works
- **Ergonomic** design
- Stroke limitation by mechanical device and electronic controlled
- Weight: Only **5.5 kg** incl. Rechargeable battery¹
- **robust** design


- Tool head **360° turnable**
- Wide range of tool heads for clinching, piercing, punching and bending
- High power Lithium-ion-rechargeable battery
- USB connection for quality control
- Main supply also by cable (220 V/110 V)

¹without C-Frame or tool head

Location South: BTM [Europe] Blechverbindungstechnik GmbH
Dieselstraße 27 · D-77833 Ottersweier
Tel.: +49 (0) 72 23/80 83 93 · Fax +49 (0) 72 23/8 08 39 50
www.btm-europe.de · info-sued@btm-europe.de

TALAS

Paardenkerkhofstraat 56 B-2800 Mechelen
Tel. +32(0)15.61.60.07 Fax. +32(0)15.61.75.27
Email. talas@talas.be www.talas.be



Rechargeable battery clinch and pierce unit ULBG 601





[Europe]
Blechverbindungstechnik
GmbH

The **BTM clinch and pierce unit ULBG 601** is been designed as a mobile and robust hand held clinch unit with a very high joining force at low handling weight. Therefore it is very adapted to a commitment at construction areas.

Due to its ergonomic and compact construction principle, easy handling is possible even with narrow dimensions.

The joining stroke is activated by one push button, when reaching the front position retract stroke will be initiated automatically. The pressing procedure can be interrupted at any time.



Technical details: ULBG 601

Weight of clinch gun ¹ :	5.5 kg
Length ² :	min. 450 mm
Width:	95 mm
Height:	310 mm
Max. clinch force	60 kN
Cycle time:	depends on stroke
Power stroke:	10-25 mm adjustable
Clinch tooling:	up to Ø 6.4 mm Tog-L-Loc®
Rechargeable battery:	14.4 V / 2.6 Ah Lithium-Ion
Battery capacity:	approx. 200 strokes <small>(depends on total stroke length)</small>
Charging time:	approx. 45 min

¹depends on C-Frame
²depends on style of tooling head

Scope of supply:
Power unit, tooling head with clinch and punch tool, rechargeable battery, charger



Location South: BTM [Europe] Blechverbindungstechnik GmbH
Dieselstraße 27 · D-77833 Ottersweier
Tel.: +49 (0) 72 23/80 83 93 · Fax +49 (0) 72 23/8 08 39 50
www.btm-europe.de · info-sued@btm-europe.de

TALAS

Paardenkerkhofstraat 56 B-2800 Mechelen
Tel. +32(0)15.61.60.07 Fax. +32(0)15.61.75.27
Email. talas@talas.be www.talas.be

www.btm-europe.de